



Guaine isolanti e fascette

Insulations sheaths and ties



T-Range: -60±200 °C

COD.	D	Cat No 1200V 200°C Thickness ()	Cat No 1500V 200°C Thickness ()	Cat No 2500V 200°C Thickness ()	Cat No 4000V 200°C Thickness ()	Cat No 7500V 200°C Thickness ()	100m/roll	
							50m/roll	
1602.001.01	0.8	0.3	0.35	0.35	0.50	0.50	100m/roll	
1602.001.02	1.0	0.3	0.35	0.35	0.50	0.50	100m/roll	
1602.001.03	1.5	0.35	0.35	0.40	0.50	0.50	100m/roll	
1602.001.04	2.0	0.35	0.35	0.40	0.50	0.50	100m/roll	
1602.001.05	2.5	0.35	0.35	0.40	0.55	0.50	100m/roll	
1602.001.06	3.0	0.35	0.35	0.40	0.55	0.50	100m/roll	
1602.001.07	3.5	0.35	0.35	0.40	0.55	0.50	100m/roll	
1602.001.08	4.0	0.40	0.40	0.45	0.60	0.50	100m/roll	
1602.001.09	4.5	0.40	0.40	0.45	0.60	0.50	100m/roll	
1602.001.10	5.0	0.40	0.40	0.45	0.60	0.50	100m/roll	
1602.001.11	5.5	0.40	0.40	0.45	0.60	0.50	100m/roll	
1602.001.12	6.0	0.40	0.40	0.45	0.65	0.50	100m/roll	
1602.001.13	7.0	0.40	0.45	0.45	0.65	0.50	100m/roll	
1602.001.14	8.0	0.45	0.45	0.50	0.70	0.50	50m/roll	
1602.001.15	9.0	0.45	0.45	0.50	0.70	0.50	50m/roll	
1602.001.16	10.0	0.45	0.50	0.55	0.70	0.50	50m/roll	

Colour	Black	White	Grey	Transp.	Blue	Red	Green	Gold	Yellow	Natural	Chrome
Material											
SGF	360	361									

EA srl

Strada degli Angariari, 25
Zona Ind. Rovereta
47891 Falciano
Repubblica di San Marino

Tel. 0549.905.778
Fax 0549.908.055
From other countries
(++)378.905.778/908.055

web: www.easrl.com
mail: ea@easrl.com

